



JETWAVE®

HIGH PRESSURE CLEANERS

Distributed by:

HUSTLER™ 270 4000 psi • 15 l/pm



Petrol Driven



Cold Water



Frequent Usage

FIELDS OF APPLICATION

- Brick Cleaning
- Painting Contractors
- Marine Anti-fouling
- Council Applications
- Cleaning Contractors
- Agricultural Equipment
- Concrete and Tradesman
- Car and Equipment Yards



The Jetwave® Hustler™ 270 is a world class cold water powered by HONDA™ petrol pressure washer for larger general cleaning. Australian engineered and assembled using only the best quality Italian and global components.



HERO INNOVATIONS



Optimise

4 x anti-vibration protection for quieter performance.



Durable

Foam filled 14" puncture proof tyres.

STANDOUT FEATURES



Professional Italian triplex Interpump delivers performance and longer life.



World class easy start HONDA™ GX390 Industrial Series OHV Engine.



Up to 6 x more abrasion resistant and anti-kink dual braid non-marking hose.



Dual M22 screw hose coupling system.



Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass and over pressurisation.



Brass washable inlet water filter.



Integrated accessory storage for hose, gun and lance.



Professional line accessories.



Jetwave Group
 72-74 Richmond Road
 Keswick | Adelaide
 South Australia | 5035 | AU
 +61 8 8371 3599
 sales@jetwave.com.au
 jetwave.com.au



STANDARD EQUIPMENT



Spray Gun
 - Industrial insulated duty back part lance and quick coupling.

Lance / Nozzle
 - Stainless steel dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" translucent steel dual braided hose with quick coupling.

OPTIONAL ACCESSORIES

1. Complete Turbo Head with Lance	p/n	JWA158
2. Additional High Pressure Hose (per metre)	p/n	52001
3. High Pressure Swivel	p/n	26105000
4. 15m Extension Hose	p/n	41071
5. LS3-1 Foaming Lance with Tank	p/n	JWA221
6. High Pressure Hose Reel (cap 30m)	p/n	1060CMPL
7. Hammerhead™ Whirlaway 20" ABS	p/n	DCFSCP20
8. Hammerhead™ Whirlaway 22" Stainless Steel	p/n	DCFSCS22Z
9. Engine Hour Meter	p/n	19598
10. Giraffe™ Telescopic Lance	p/n	DCLTG24A4
11. Sandblasting Kit	p/n	JWA164
12. Sludge Kit	p/n	80005
13. Drain Kit	p/n	HOP3X20



POWERED by HONDA™

The manufacturer reserves the right to modify design features and technical facts without notice, due to our principals of continuous improvement.

V1.0 8/2017

Product Code	p/n	HP270-15P
--------------	-----	-----------

TECHNICAL DATA

Working Pressure	psi / bar	4000 / 280
Flow Rate	l/pm	15
Max Water Inlet Temp	°c / °f	60 / 140

INTENDED APPLICATION

Usage Frequency	hours / type	2 - 4 daily / Intermittent
Category of Dirt / Debris	type	Medium

MOTOR FEATURES

Engine	type	HONDA™ GX390 (4 stroke, air cooled)
Power	hp / cc	13 / 390
Fuel Supply	type	Unleaded
Fuel Capacity	litres	6.1
Low Oil Shutdown	y / n	Y
Starting System	type	Recoil / Pull

HYDRAULIC FEATURES

Pump / Head / Pistons	type	Interpump Plunger Triplex / Brass / Ceramic
Motor Pump Coupling	type	Direct Drive
Pump Speed	rpm	3400
Unloader Valve	type	Integral
Safety Valve	y / n	Y
Orifice / Nozzle	size	040

OTHER FEATURES

Electric / Key Start Available	y / n	N
Adjustable Pressure	y / n	Y
Hose Reel Provision	y / n	Y
Frame Structure	type	Welded hot dipped galvanised 4 wheel roll
Onboard Accessory Storage	y / n	Y
Defergent Injector	y / n	Y - Downstream low pressure

DIMENSIONS & WEIGHT

Approx Weight	kg	72 unit / 76 boxed
Unit Dimensions	mm	1010(L) x 700(W) x 850(H)
Boxed Dimensions	mm	970(L) x 600(W) x 670(H)
Number per Pallet	type: pieces	AS: 2 / Euro: 1

WARRANTY(S)

Engine Warranty	years	GX4 YEAR WARRANTY
Limited Pump Warranty	years	2
Limited Frame Warranty	years	5
Limited Accessory Warranty	days	90

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).