

GH6000E 7.5kVA HONDA

7.5kVA
HONDA
GH6000E



ENGINE

MANUFACTURER	Honda
ENGINE MODEL	GX390E
TYPE & CYLINDER	O.H.V.
STARTING	Electric Start
RUN TIME	2.6hr @ 100%, 3.8hr @ 60% load
FUEL	Unleaded Petrol
CUBIC CAPACITY	389 cm ³
HP 3000 RPM CONT	8.0HP
OIL CAPACITY	1.1L

TECHNICAL

MODEL	GH6000E
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBA @7m see *1		
	kW	kVA	dBA		
3000RPM	6.0	7.5	72	6.1L	7.5kVA

ADDITIONAL INFO

OUTLETS 10amp + 15 amp
switched with thermal overload

FRAME Extra large roll frame

DIMENSIONS

LENGTH	85cm
WIDTH	57cm
HEIGHT	60cm
WEIGHT	75kg

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

OPTIONS

- Hire Spec: 2 x IP66 rated outlets, circuit breaker & RCD protection.
- 2 or 4 wheel kit
- Extra large roll frame
- Long Range Tank