

GKD5600E-MINE SPEC

7kVA KOHLER

7kVA
KOHLER
GKD5600E-MS



ENGINE

MANUFACTURER	Kohler
ENGINE MODEL	KD440E/10.2
TYPE & CYLINDER	O.H.V. Single Cylinder
STARTING	Recoil & Electric Start
RUN TIME	2.3hr @ 100%, 3.2hr @ 75% load
FUEL	Diesel
CUBIC CAPACITY	442 cm3
HP 3000 RPM CONT	10HP
OIL CAPACITY	1.5L

TECHNICAL

MODEL	GKD5600E-Mine Spec
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBA @7m see *1		
	kW	kVA	dBA		
3000RPM	5.6	7	80	5L	7kVA

ADDITIONAL INFO

OUTLETS	10amp or 15amp IP66 C/B RCD
FRAME	Heavy duty roll frame

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

DIMENSIONS

LENGTH	85cm
WIDTH	55cm
HEIGHT	60cm
WEIGHT	96kg

INCLUSIONS

- 2xIP56 rated outlets, circuit breaker & RCD protection
- 1 kg fire extinguisher
- Bundled tray, centre lift & earth stake
- Sealed battery & covered box
- Lockable starter motor & battery isolator
- Jump start receptacle
- Drip tray and emergency stop
- BMA Certification Optional