

GYD2000E-MINE SPEC

2.2kVA YANMAR

2.2kVA
YANMAR
GYD2000E-MS



ENGINE

MANUFACTURER	Yanmar
ENGINE MODEL	L48 AE-DEG
TYPE & CYLINDER	O.H.V. Single Cylinder
STARTING	Recoil & Electric Start
RUN TIME	3.12hr @ 100%, 4.1hr @ 75% load
FUEL	Diesel
CUBIC CAPACITY	296 cm3
HP 3000 RPM CONT	3.8HP
OIL CAPACITY	1.1L

TECHNICAL

MODEL	GYD2000E-Mine Spec
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBa @7m see *1		
	kW	kVA	dBa		
3000RPM	2	2.2	80	2.5L	2.2kVA

ADDITIONAL INFO

OUTLETS	10amp or 15amp IP66 C/B RCD
FRAME	Heavy duty roll frame

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

DIMENSIONS

LENGTH	67cm
WIDTH	44cm
HEIGHT	48cm
WEIGHT	54kg

INCLUSIONS

- 2xIP56 rated outlets, circuit breaker & RCD protection
- 1 kg fire extinguisher
- Bundled tray, centre lift & earth stake
- Sealed battery & covered box
- Lockable starter motor & battery isolator
- Jump start receptacle
- Drip tray and emergency stop
- BMA Certification Optional